



# Mastek Snap Tite Lay Flat



## Tensile Strength of Snap Tite PU Hosing

Size	Nom ID (in)	Reinf Plies	Nom Wall Thickness (in)	Approx Wt		Max Rec WP*		Min Burst Pressure		Std Pack (metres)
				(lb/m)	(kg/m)	(psi)	(bar)	(psi)	(bar)	
1-1/4"	1-1/4"	1	0.085	0.497	0.225	450	31.0	900	62.1	200
1-1/2"	1-1/2"	1	0.085	0.730	0.331	450	31.0	900	62.1	200
1-3/4"	1-3/4"	1	0.090	0.794	0.360	450	31.0	900	62.1	200
2"	2"	1	0.090	0.900	0.408	450	31.0	900	62.1	200
2-1/2"	2-1/2"	1	0.090	1.279	0.580	450	31.0	900	62.1	200
3"	3"	1	0.130	1.656	0.751	350	24.1	700	48.3	200
3-1/2"	3-1/2"	1	0.130	2.130	0.966	250	17.2	500	34.5	200
4"	4"	1	0.130	2.507	1.137	270	18.6	540	37.2	200
4-1/2"	4-1/2"	1	0.130	2.745	1.245	250	17.2	500	34.5	200
5"	5"	1	0.130	3.124	1.417	250	17.2	500	34.5	200
6"	6"	1	0.120	3.785	1.717	300	20.7	600	41.4	200



### Storz Coupling

- No male or female ends allowing connection from either end.
- Quick release.
- More compact allowing more Lay Flat Hosing on the reel.
- Heavy Duty and long lasting.
- Unique swivel which prevents twists.

Mastek Ltd.  
Cootehill Business Park  
Cootehill, Co. Cavan  
Ireland, H16DX45

Tel. +353 49555953  
Fax. +353 49555954

E-mail, [enquiries@mastek.ie](mailto:enquiries@mastek.ie)  
Website, [www.mastek.ie](http://www.mastek.ie)  
Facebook, see Slurry Mate



# Mastek Snap Tite Lay Flat

Mastek Ltd.  
Cootehill Business Park  
Cootehill, Co. Cavan  
Ireland, H16DX45

Tel. +353 49555953  
Fax. +353 49555954

E-mail, [enquiries@mastek.ie](mailto:enquiries@mastek.ie)  
Website, [www.mastek.ie](http://www.mastek.ie)  
Facebook, see Slurry Mate