



 **Snap-Tite**
HOSE

Soil Mate

Slurry Mate

Industrial Hose Polyurethane Lay Flat Hose

Proven Quality, Backed by Superior Customer Service

Snap-tite Hose - Polyurethane Lay Flat Hose

Rugged Constructions for Diverse Applications

Snap-tite Hose polyurethane lay flat hose provides compact, durable, lightweight water and multipurpose service in agricultural, construction, general industrial and mining applications. The hose offers superior value due to its robust design, rugged materials, compatibility with multiple media and versatility across many applications.

Traditional PVC lay flat hose incorporates spiral reinforcement sandwiched between stiff layers of

PVC, whereas Snap-tite Hose provides a strong circular woven reinforcement that allows the polyurethane to be extruded through-the-weave, fully encapsulating the textile reinforcement. The strong yet pliable hose wall resists abrasion, cracking, puncturing, and degradation from oil, ozone, petrochemicals, ultraviolet light and weathering. The design and materials promote strong adhesions between the hose components, resulting in exceptional performance and service life.

Snap-tite Hose offers distinct styles for targeted service:

- **TE** for industrial applications
- **AS** incorporates dual antistatic wires for grounding a static charge
- **IR** for irrigation
- **PW** for potable water
- **TS** features a thick wall for slurry applications

All (except PW) are offered with optional standard colours for easy identification, and the flexible lay flat construction rolls up for easy handling, transportation and storage.

General Specifications

Hose Construction:	Polyurethane extruded through one woven polyester ply of reinforcement (AS hose contains dual antistatic wires)
Temp Range:	-40°C to +80°C (-40°F to +176°F)
Brand Method:	Black or white text
Brand Example:	SNAP-TITE HOSE (PART NUMBER) (DATE CODE) MADE IN IRELAND MAXIMUM WORKING PRESSURE (XXX)
Packaging:	PSI Coils (maximum 100 meters) or flaked in cartons

TE Blue Multipurpose Hose



TE is a standard duty water discharge and transfer hose for general industrial applications.

PW (Potable Water) Hose is a distinct version of TE hose for potable water service.

PW hose has been fully tested to prove compatibility with potable water, including taste and odor. It is used in mobile applications to transfer large volumes of drinking water from tank trucks to major public events or work sites, as well as emergency water supply lines to bypass water mains where service has been curtailed due to construction. PW hose is much easier to couple, install and remove than polyethylene pipe, and is resistant to petrochemical ingress and resulting water contamination.

PW hose meets the following standards/requirements:

- England, Northern Ireland and Wales: Approved for use in public water supplies per the Secretary of State's List of Approved Products, listing 56/4/62, as published by the Drinking Water Inspectorate (DWI).
- Poland: National Institute of Public Health listing HK/W/0105/01/2009.
- Scotland: Approved by the Scottish Ministers per Water Supply (Water Quality) (Scotland) Regulations 2001, Regulation 27/4.
- UK Private Schemes: Water Regulations Advisory Scheme (WRAS) Approval Number 0710512.
- USA: Meets and exceeds standard NSF 61 for potable water.

Size	Nom ID (in)	Reinf Plies	Nom Wall Thickness (in)	Approx Wt (lb/m) (kg/m)		Max Rec WP* (psi) (bar)		Min Burst Pressure (psi) (bar)		Std Pack (meters)
1-1/4"	1-1/4	1	0.085	0.497	0.225	450	31.0	900	62.1	200
1-1/2"	1-1/2	1	0.085	0.730	0.331	450	31.0	900	62.1	200
1-3/4"	1-3/4	1	0.090	0.794	0.360	450	31.0	900	62.1	200
2"	2	1	0.090	0.900	0.408	450	31.0	900	62.1	200
2-1/2"	2-1/2	1	0.090	1.279	0.580	450	31.0	900	62.1	200
3"	3	1	0.130	1.656	0.751	350	24.1	700	48.3	200
3-1/2"	3-1/2	1	0.130	2.130	0.966	250	17.2	500	34.5	200
4"	4	1	0.130	2.507	1.137	270	18.6	540	37.2	200
4-1/2"	4-1/2	1	0.130	2.745	1.245	250	17.2	500	34.5	200
5"	5	1	0.130	3.124	1.417	250	17.2	500	34.5	200
6"	6	1	0.120	3.785	1.717	300	20.7	600	41.4	200

For TE hose for Potable Water (PW) service, specify when ordering. * Or rating of coupler, whichever is lower

Part Number Example: TE15X200MB

TE 15 200M B
Hose ID Length Colour
(1-1/2") (meters) (blue)

Optional Standard Colours:

K **G** **NG**
Black (K) Green (G) NATO Green (NG)
R **Y**
Red (R) Yellow (Y)

Part Number Example: TE15X200MBPW

TE 15 200M B PW
Hose ID Length Colour (Potable Water)
(1-1/2") (meters) (blue) (Water)

Optional Standard Colours: None; available in blue only

IR Blue Irrigation Hose



IR is a standard duty irrigation hose for water discharge and transfer in agricultural applications.

Size	Nom ID (in)	Reinf Plies	Nom Wall Thickness (in)	Approx Wt (lb/m) (kg/m)		Max Rec WP* (psi) (bar)		Min Burst Pressure (psi) (bar)		Std Pack (meters)
1-1/4"	1-1/4	1	0.085	0.497	0.225	450	31.0	900	62.1	200
1-1/2"	1-1/2	1	0.085	0.730	0.331	450	31.0	900	62.1	200
1-3/4"	1-3/4	1	0.090	0.794	0.360	450	31.0	900	62.1	200
2"	2	1	0.090	0.900	0.408	450	31.0	900	62.1	200
2-1/2"	2-1/2	1	0.090	1.279	0.580	450	31.0	900	62.1	200
3"	3	1	0.130	1.656	0.751	350	24.1	700	48.3	200
3-1/2"	3-1/2	1	0.130	2.130	0.966	250	17.2	500	34.5	200
4"	4	1	0.130	2.507	1.137	250	17.2	500	34.5	200
4-1/2"	4-1/2	1	0.130	2.745	1.245	250	17.2	500	34.5	200
5"	5	1	0.130	3.124	1.417	250	17.2	500	34.5	200
6"	6	1	0.120	3.785	1.717	300	20.7	600	41.4	200

Part Number Example: IR15X200MB

IR 15 200M B
Hose ID Length Colour
(Irrigation) (1-1/2") (meters) (blue)

* Or rating of coupler, whichever is lower

Optional Standard Colours:

K **G** **NG** **R** **Y**
Black (K) Green (G) NATO Green (NG) Red (R) Yellow (Y)

TS Brown Slurry Hose



TS is a heavy duty slurry discharge and transfer hose. The hose construction features a thick wall for additional abrasion resistance and durability in rugged slurry transfer applications.

Size	Nom ID (in)	Reinf Plies	Nom Wall Thickness (in)	Approx Wt (lb/m) (kg/m)		Max Rec WP* (psi) (bar)		Min Burst Pressure (psi) (bar)		Std Pack (meters)
3"	3	1	0.150	2.035	0.923	350	24.1	700	48.3	200
4"	4	1	0.150	2.934	1.331	250	17.2	500	34.5	200
4-1/2"	4-1/2	1	0.150	3.124	1.417	250	17.2	500	34.5	200
5"	5	1	0.150	3.503	1.589	250	17.2	500	34.5	200
6"	6	1	0.150	4.023	1.825	300	20.7	600	41.4	200

Part Number Example: TS30X200MN


TS 30 200M N
Hose ID Length Colour
(Slurry) (3") (meters) (brown)

* Or rating of coupler, whichever is lower

Optional Standard Colours:

K **G** **NG** **R** **Y**
Black (K) Green (G) NATO Green (NG) Red (R) Yellow (Y)

AS Yellow Antistatic Hose



AS is a discharge and transfer hose for fluids that develop electrical charges when flowing through the hose. AS hose incorporates dual antistatic wires that provide a path to conduct an electrical charge to ground. The distinctive bright yellow cover provides instant identification from multiple angles and great distances.

Size	Nom ID (in)	Reinf Plies	Nom Wall Thickness (in)	Approx Wt (lb/m) (kg/m)		Max Rec WP* (psi) (bar)		Min Burst Pressure (psi) (bar)		Std Pack (meters)
1-1/2"	1-1/2	1	0.085	0.730	0.331	400	27.6	800	55.2	200
2"	2	1	0.090	0.900	0.408	450	31.0	900	62.1	200
2-1/2"	2-1/2	1	0.090	1.279	0.580	300	20.7	600	41.4	200
3"	3	1	0.130	1.656	0.751	300	20.7	600	41.4	200
4"	4	1	0.130	2.507	1.137	250	17.2	500	34.5	200
6"	6	1	0.120	3.785	1.717	300	20.7	600	41.4	200

Part Number Example: TE15X200MYAS

TE 15 200M Y AS
Hose ID Length Colour (Anti Static)
(1-1/2") (meters) (yellow)

* Or rating of coupler, whichever is lower

Optional Standard Colours:

K **N** **G** **NG** **R**
Black (K) Brown (N) Green (G) NATO Green (NG) Red (R)

Chemical Resistance Guide for TE & IR Hose

Key: G = Good • F = Fair • C = Conditional • X = Not Recommended

Chemical	Resistance	Chemical	Resistance	Chemical	Resistance
Acetone	X	Ethyl Ether	C	Phosphoric Acid (Crude)	X
Ammonium Hydroxide	X	Ethylene Dichloride	X	Phosphoric Acid 45%	X
Amyl Acetate	C	Freon 113	G	Potassium Hydroxide	C
Benzene	X	Fuel Oil	F	Propyl Alcohol	C
Benzyl Alcohol	X	Fuel Oil Acid	C	Sodium Chloride	F
Butyl Acetate	G	Gasoline (Sour or refined)	G	Sodium Hydroxide (Caustic Soda)	C
Butyl Alcohol	G	Glue	G	Sodium Nitrate	G
Butyl Stearate	F	Grease	G	Sodium Phosphate	X
Calcium Chloride	G	Hydrochloric Acid (Hot) 37%	X	Sodium Silicate	G
Calcium Nitrate	G	Hydrochloric Acid (Cold) 37%	X	Sulphuric Acid 10%	C
Carbon Tetrachloride	X	Hydrogen Gas	G	Sulphuric Acid 11-75%	C
Chlorobenzene	X	Hydrogen Peroxide 90%	C	Sulphuric Acid 76-95%	C
Chloroform	X	Hydrogen Peroxide 3%	G	Toluene (Toluol)	X
Cresols	X	Kerosene	G	Trichloroethylene	C
Chlorox	C	Methyl Alcohol	C	Tricresyl Phosphate	X
Detergents (Non-hydrocarbon)	G	Methyl Ethyl Ketone (MEK)	X	Vegetable Oils	G
Diacetone Alcohol	X	Mineral Oil	G	Water, Fresh	G
Diesel Oil	G	Naphtha	F	Water, Sea	G
Diethylene Glycol, cold	G	Nitric Acid	X	Zinc Chloride, Dry	G
Ethyl Alcohol, (Ethanol) cold	G	Petroleum, Crude	G	Zinc Sulphate, Dry	G
		Phenol (Carbolic Acid)	C		

WARNING! The above data is based on testing and believed to be reliable; however, the information should be used ONLY as a guide, since it does not take into consideration all variables, such as elevated temperatures, fluid contamination, concentration, etc., that may be encountered in actual use. All critical applications should be tested. Contact Snap-tite Hose for additional chemical compatibility information.

NOTE: For TE hose for Potable Water (PW) service, specify when ordering.

© 2017 AAH Europe Hose Company Limited

Information and specifications subject to change without notice and without liability therefore. Trademarks used herein are the property of their respective owners.

 Snap-tite
HOSE

AAH Europe Hose Company
Limited,
Whitemill Industrial Estate,
Wexford,
Ireland

Telephone: +353 5391 84449
jgahan@Snap-titehose.com
rmcgrath@Snap-titehose.com
www.Snap-titehose.com

 Soil Mate
MASTEK
Slurry Mate

Mastek Ltd,
Cootehill Business Park,
Cornacarrow,
Cootehill,
Co Cavan,
Ireland

Telephone: +353 49555 5953
enquiries@mastek.ie
www.mastek.ie